

**TITLE: Applications of user-to-user information transfer between telecommunication devices**

5 **TECHNOLOGICAL FIELD**

The invention relates to the communication of information between telecommunication devices transparently through a network. Especially the invention concerns the applications of User-to-User Signalling (UUS).

10

**BACKGROUND OF THE INVENTION**

15 The term signalling generally refers to transmitting, from one telecommunication device to another, some information that relates more to the management of the communication connection than directly to the payload, like speech or data, for the transmission of which the communication connection between the devices has been established. For example in mobile telephony signalling is used to exchange measurement results, announcements, commands and short messages between a  
20 mobile terminal and a base station, or between the different devices belonging to the fixed parts of the mobile telephone network.

User-to-User Signalling or UUS is a procedure recently disclosed as a supplementary service in some advanced telephone systems. Its intended use is the  
25 transmission of a limited amount of subscriber generated information (UUI; User-to-User Information) to and/or from another user in association with a call between the users concerned. The nature of UUS dictates that the network that mediates the communication between the users does not interpret the UUI or act upon it in any way, i.e. it is passed "transparently" through the network. This patent application  
30 will refer to the known aspects of UUS in the form in which they have been disclosed in the document "GSM 02.87: GSM Digital Cellular Telecommunications System (Phase 2+); User-to-User Signalling (UUS); Service Description, Stage 1, v.5.2.1", which has been published by ETSI (European Telecommunications Standards Institute) in November 1997 and which is incorporated herein by  
35 reference. However, the invention is applicable in association with all current and future telecommunication systems which support user-to-user signalling in a form comparable to that described below.

00412897 100599 665001 662760

There are, at the time of filing this patent application, three subclasses of UUS, namely Service 1, Service 2 and Service 3. A user has access to these services as described in his/her subscription contract with the system operator. According to Service 1, UUI can be sent and received during call setup and termination by embedding UUI into the appropriate call control messages. Service 1 can be an implicit part of each call setup, whereby the user does not have to initiate the transmission of a UUS message separately, or it may be explicit in which case the user has to initiate an appropriate procedure. Service 2 encompasses the UUS messages that are sent and received after the calling party has received an indication that the called party has been informed of the call, but before the call is actually established. The network is not responsible for delivering a sent Service 2 message to its recipient before the call will be established. All such UUS messages that are sent and received during an established call connection belong to Service 3.

For example an ISDN system (Integrated Services Digital Network) allows as a network option the transfer of UUI with a maximum length of 32 octets for Service 1. The endpoints of a point-to-point connection where UUS is used may be mobile-to-mobile, mobile-to-PLMN (Public Land Mobile Network), mobile-to-ISDN network, mobile-to-ISDN terminal, or mobile-to-PSTN (Public Switched Telephone Network). If the other end is PLMN, ISDN network or ISDN terminal, it must be equipped with sufficient ISUP (ISDN Signalling User Part) signalling support known as such to the person skilled in the art. If the other end is PSTN, it must be equipped with sufficient inter-exchange ISUP signaling support known as such to the person skilled in the art.

The prior art publications disclose only a very limited number of actual applications for UUS. It is therefore an object of the invention to present a method and the necessary equipment for providing added value to a telephone connection by using specific applications of UUS.

## SUMMARY OF THE INVENTION

The objects of the invention are achieved by presenting a certain inner structure for an UUS message, and associating certain information elements within UUS messages with the suggested use of the contents of a received UUS message.

It is characteristic to the method according to the invention that it comprises the steps of

- initiating a telephone connection between a transmitting telecommunication device and a receiving telecommunication device,
- 5 - composing, at said transmitting telecommunication device, a signalling message of predetermined form to be transmitted in association with the telephone connection, said signalling message containing additional information which is to complement the telephone connection,
- indicating, within said signalling message, the intended receiving part within said
- 10 receiving telecommunication device of at least part of said signalling message and
- transmitting said signalling message from said transmitting telecommunication device to said receiving telecommunication device.

15 The invention also applies to a telecommunication device for the transmission of signalling and payload information. It comprises a transceiver unit, a unit for processing received payload information, a unit for processing payload information to be transmitted, and a control block. The transceiver unit is arranged to direct received signalling information to the control block and to take signalling information to be transmitted from the control block. It is characteristic to the

20 invention that it comprises a signalling unit arranged to compose a signalling message of predetermined form to be transmitted in association with a payload information transmission connection, and to indicate, within said signalling message, the intended receiving part within another telecommunication device of at least part of said signalling message.

25 The limited applicability of known UUS arises from the concept of using UUS only to transmit human-readable character strings from the transmitting user to the receiving user. For example in the known ISDN applications it is assumed that the receiving user has a terminal that contains a display so that it may reveal the

30 contents of a received UUS message to the user in the form of a character string. However, even the present terminals include a large number of other functional blocks than the display, and it is expected that in the near future a large number of completely new terminal types will emerge, combining at least some of the features of a video telephone, portable telefax, palmtop computer, positioning device and

35 many other portable electronic devices previously known as separate units. Additionally the receiving device of an UUS message may be some other device in the network than a terminal.

According to the invention an inner structure is given to a UUS message, whereby specific parts of the message may be used to identify the intended target of the message within the receiving device and/or the intended use of the contents of the message. The message may contain a human-readable character string, a number of  
 5 undisplayable and/or unreadable characters, a passage of binary code only intelligible to computers operating under a certain program or protocol, a digitised waveform or some other information of unlimited nature. The intended target of the message may be a display, a processor, a register or memory location, an application program, a loudspeaker or some other specified functional block, or the message  
 10 may leave it to the discretion of the receiving device to direct the contents of the message to a suitable block.

#### BRIEF DESCRIPTION OF DRAWINGS

15 The novel features which are considered as characteristic of the invention are set forth in particular in the appended Claims. The invention itself, however, both as to its construction and its method of operation, together with additional objects and advantages thereof, will be best understood from the following description of  
 20 specific embodiments when read in connection with the accompanying drawings.

Fig. 1 illustrates the concept of transmitting an UUS message,

Fig. 2 illustrates an advantageous inner structure of an UUS message according  
 25 to the invention, and

Fig. 3 illustrates an advantageous terminal structure according to the invention.

#### 30 DETAILED DESCRIPTION OF THE INVENTION

To facilitate full understanding of the invention we will first briefly refer to Fig. 1, where the terminal 101 of a first user is transmitting a UUS message to the terminal 102 of a second user. For the sake of example we may assume that terminal 101 is a  
 35 mobile terminal resembling the known Nokia 9000 Communicator in a digital cellular radio system 103, and terminal 102 is a multifunctional office ISDN terminal comprising the known features of a desktop computer, telefax and telephone. In Fig. 1 it has been assumed that the cellular radio system 103 is GSM

5

10

20

35

exchange. Fig. 2 proposes an alternative solution, which does not require such a negotiation procedure. The exemplary UUS message 200 of Fig. 2 consists of a number of fields, of which a Protocol Discriminator (PD) field 201, a Data Coding Scheme (DCS) field 202, an Control Field Length Indicator (CFLI) field 203, three  
 5 Control Fields (CF) 204, 205 and 206 as well as a data field 207 are shown. Of these, the PD and DCS fields together indicate, what kind of protocol and what kind of coding scheme have been used in the preparation of the message, and the CFLI field indicates the combined length of the header fields (all fields except the data field). The data field 207 is, as its name indicates, the field that contains the actual  
 10 data for the transmission of which the UUS message has been composed.

The CF fields (which may also be called Information Element fields; IE), may be used to transmit several kinds of information like sequence numbering of several consecutive messages. However, a very specific use of the CF fields is closely  
 15 associated with the broadening of the UUS application possibilities suggested by the present invention. Depending on the contents of the data field, the part of the receiving terminal that is supposed to handle or take advantage of the UUS message may vary. The CF fields are most advantageously used to transmit the identification of the functional block in the receiving device to which the UUS message is  
 20 destined or the specific intended action that the receiving device is supposed to do and to which the contents of the UUS message are related.

If we apply the invention to the purpose of transmitting a displayable text message, which is the previously known application of UUS messages, the contents of the  
 25 fields of Fig. 2 might be as follows.

PD field 201: a code identifying the conventional UUS text message transmission as the applicable protocol.

30 DCS field 202: a code identifying ASCII as the coding scheme.

CFLI field 203: a binary number indicating the combined length of the PD, DCS, CFLI and CF1 fields in octets.

35 CF1 204: a code identifying the display as the intended receiving functional block within the receiving device.

DATA 207: the text message as an ASCII character string.

It is easy to generalize the above-presented way of utilizing the fields for identifying an arbitrary protocol, coding scheme and intended receiving functional blocks or processes. The invention does not limit the selection of codes that are used to  
5 identify them. However, to avoid confusion, it is recommendable that a standard selection of codes will be established within or in association with an internationally recognised telecommunications standard.

It should be understood that the invention does not require the above-mentioned  
10 fields to appear in each and every UUS message. For example backward compatibility with previously known UUS schemes is easily provided by defining that if the contents of the PD field indicate "IA5 chars" as in a prior art UUS message, no other header or control fields are present in the message and it will be handled like a conventional UUS message (the contents of the data field  
15 immediately following the PD field are understood as a string of displayable characters). If the PD field indicates some other protocol, such receiving devices that do not support the indicated protocol simply handle the UUS message as a badly received (corrupted) UUS message, which typically means that they discard the message and do not take any further action.

20 Fig. 3 illustrates a simplified terminal structure 300 that is advantageously used for transmitting and/or receiving structured UUS messages according to the invention. The terminal is a telephone device and comprises a transceiver 301 for transmitting and receiving information over a physical link 302, which may as such be a radio  
25 link, a wireline connection, an infrared link or some other known physical link; the transceiver comprises the necessary means known as such for arranging for the information input at the TX lines to be transmitted over the physical link and information received over the physical link to be output at the RX lines. Connected to the TX and/or RX lines there are a speech recording unit 303, a speech  
30 reproduction unit 304 and a control block 305. The latter is additionally coupled to a display 306, a memory 307 and a keyboard 308. The receiver side of the transceiver 301 is arranged to separate received signalling (UUS along with all other signalling) from received speech frames and to direct signalling to the control block 305 and speech frames to the speech reproduction unit 304. Similarly the transmitter side of  
35 the transceiver 301 is arranged to take speech frames to be transmitted from the speech recording unit 303 and signalling to be transmitted from the control block 305.

Within the control block 305 there is a UUS unit 310 for transmitting and receiving UUS messages. The receiving side of the UUS unit is capable of identifying, from a received UUS message, the protocol and coding scheme that have been used for creating the message. Additionally the receiving side of the UUS unit is capable of  
5 identifying, from the contents of the CF fields in a received UUS message, the functional block or process that is the intended recipient of the data part of the message. On the basis of the latter identification the UUS unit directs the data part of a received UUS message in a suitably decoded form to the correct functional block or process. The transmitting side of the UUS unit is capable of taking a piece  
10 of information from the keyboard, from the other parts of the control block or from some other part of the terminal and formatting it into a UUS message to be transmitted. In the process of formatting the UUS message, the transmitting side of the UUS unit uses its knowledge about the appropriate codes for identifying a protocol, a coding scheme and an intended receiving functional block or process in  
15 the device to which the UUS message is to be transmitted. The codes for identifying a protocol, a coding scheme and an intended receiving functional block or process are most advantageously stored in the memory 307 as a look-up table 311.

The functions represented as the UUS unit in Fig. 3 are most advantageously  
20 implemented by programming them as an executable program for a microprocessor, which as such is within the capabilities of a person skilled in the art.

The invention has been described above solely with reference to the UUS specifications as they appear in the appropriate standards mentioned in the  
25 description of prior art. However, the invention is equally well applicable to other systems where short messages are used in association with telephone or dataphone connections to transmit call-related information between two endpoints without the network between them reacting on the messages in any other way than by providing the means for their transmission.

09442897-100599